



Crane Level Indicator

Cost-effective solutions / Worldwide support / Quality and innovation



The Robway Crane Level Indicator provides a graphical level indication and out-of-level warnings for both OEM and retrofit applications. The Crane Level Indicator capability optionally provides outrigger monitoring. Monitoring these conditions can help assure the operator that he is operating within the manufacturer's load chart.

- ▶ Crane Tilt within $\pm 0.1^\circ$
- ▶ Zoom in / Zoom out for fine-tuning
- ▶ Asymmetric Outrigger Monitoring
- ▶ CAN bus Data Interface
- ▶ In-Dash mount or RAM mount



Robway Crane Level Indicator

Specifications

DISPLAY	Screen	4.3" diagonal 480 x 272 resolution	
	Mechanical	142 x 98 x 43.2mm (W x H x D) PC+ABS material 0.40 kg	0.9 lbs
	Environmental	-30°C to +75° C operating temp IP 65	
	Interface	Two CAN bus channels CAN bus 2.0 B Up to 1 Mbps	
TILT SENSOR	Type	Dual axis	
	Range	± 45 Degrees	
	Accuracy	≤ ± 0.05°	
	Mechanical	90 x 62 x 34 (L x W x H) 0.42 kg Diecast zinc nickel-plated	
	Environmental	-40°C to +85° C operating temp IP 65 / 67/ 68 / 69K	
OUTRIGGER INTERFACE	Signal Inputs	0-5V, 0-10V, 4-20mA	
	Mechanical	10 118x 133 x 37 mm (W x L x H excluding plugs) 0.25 kg	
	Environmental	Nylon housing -40°C to +85° C operating temp IP 67	
SYSTEM POWER	Voltage	9 – 30 VDC	
	Current	< 1 amp	

To order, please contact
sales@robway.com
or call +61 8 8238 3500